## **AC49 Metalized DUCTape** 11 MIL METALIZED MEDIUM GRADE DUCT TAPE

# INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

### DESCRIPTION

Metalized polyethylene (PE) film applied to high tensile cloth with an aggressive pressure sensitive natural rubber adhesive. Designed for applications where a high quality grade of cloth tape is required and the appearance of metalized backing is preferred.

## **PRODUCT APPLICATION**

HVAC (heating, ventilation and air conditioning) applications. Metalized coating helps protect tape from UV and blends in where bright finished ductwork is left exposed. An excellent choice for minor repairs on flexible duct and reflective insulation.

#### **GOVERNMENT COMPLIANCE**

Meets HUD, BOCA and L.A. County codes. Tested in accordance with UL-723.



intertape polymer group®

100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 03/11

#### **NOMINAL VALUES**

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Metalized PE coated cloth
Natural Rubber/Resin
19 (83.2 N/25mm)
17
55 (15 N/25mm)
11.0 (0.28mm)
Metalized Silver

