Poly Repair Tape INDOOR/OUTDOOR CLEAR REPAIR TAPE

DESCRIPTION

Heavy-duty polyethylene coated cloth tape with an aggressive synthetic rubber pressure-sensitive adhesive. Excellent for low temperature bonding. The permanently tacky adhesive adheres well to most surfaces under a wide range of conditions. Moisture resistant. Conformable and maintains a tight water seal in all weather conditions.

PRODUCT APPLICATIONS

For temporary repair or splicing of polyethylene sheeting, home, office, recreational repairs and surface protection. Wrapping & sealing, binding & bundling, and general maintenance.

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	5.5 mil PE film
Adhesive	Synthetic Rubber/Resin
Tensile Strength (Ibs/in of width)	22 (96 N/25mm)
Elongation (% at break)	100
Initial Adhesion to Steel (oz/in of width) (20 min @ RT)	70 (19 N/25mm)
Adhesion to Backing (oz/in of width) (20 min @ RT)	35 (9.6 N/25mm)
Shear Adhesion (hours) (2lb/in² of width)	76
Total Thickness (mils)	9.0 (0.23mm)
Color	Clear



intertape polymer group®

100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.



