



Shown with optional infeed and exit tables

RSA 3036-SB

RANDOM SEMI-AUTOMATIC CASE SEALER

Interpack's RSA Series Case Sealers are operator-fed machines that automatically adjust for each size case processed. An Interpack™ random case sealer is your solution when production has a need for different sized cases to be processed through a single case sealer. Every Interpack™ case sealer comes with ET 2Plus tape heads with adaptive technology to provide optimal tape application and wipe down to each of the three taped panels of the case.

Specifically designed to process a larger range of cases, this oversized side belt drive random case sealer contains the same package of features and benefits as the standard sized RSA 2024-SB. Construction is reinforced to handle larger, heavier cases. Standard 4" tall drive bases provide twice the gripping power.

When you compare features, benefits and value, Interpack Case Sealers are the right choice for operators, plant engineers, maintenance and purchasing.



ET 2Plus tape head


MACHINE FEATURES & BENEFITS

- Heavy duty construction will process up to 85 lb cases with dual columns for maximum processing stability
- 4" tall drive bases standard
- 2 modes of operation - upper head retained random mode & bottom only seal mode
- Pneumatic infeed gate assures proper positioning of the case during processing and drastically reduces jams
- Twin 1/3 HP high torque gear motors process larger, heavier cases
- Self-tensioning, self-tracking belt drive simplifies belt replacement
- Offset tape heads process cases as low as 5"
- Unique "Clear" push button to clear jams and replace bottom tape roll

THESE MACHINES ARE ENGINEERED TO PROVIDE:

- World class performance features
- Heavy duty construction for 24/7 operation
- Ergonomic, user friendly operation and case size set up

Scan for more information on Interpack's RSA Series, including CAD drawings, manuals and videos!



800-474-8273 | itape.com




PRODUCT ATTRIBUTES

CHARACTERISTICS	RSA 3036-SB
Min Case (L x W x H)	6" x 5.75" x 5"
Max Case (L x W x H)	Inf x 30" x 36"
Case Weight	0 - 85 lbs
Belt Speed	82 ft/min
Electric	110v., 1ph., 60hz., 6A., (2 x 1/3HP)
Compressed Air Requirements	9 CFM @ 90 PSI
Tape Width	48 - 72 mm (2" - 3")
Conveyor Height	24" - 30"
Machine Weight	816 lbs crated
Machine Dimensions	44.5" x 47.5" x 83"



1
"Clear" button for jams & replacing bottom tape roll (Opposite Side of Machine)




2
1/3 HP motors for heavy duty usage



3
Top & bottom or bottom only seal operation modes



4
Digital pneumatics to improve throughput speed



5
Standard 4" tall side belts



6
Self-tensioning & tracking side drives simplify belt replacement



7
Offset tape heads process 2" high cases



8
Optional swivel & locking casters

OPTIONS & ACCESSORIES

- 3-inch wide tape heads
- Heavy-duty casters
- Infeed & exit tables (shown above)
- ET Xtreme™ tape heads

DID YOU KNOW?

IPG® is the only North American manufacturer of all 3 types of pressure-sensitive adhesives. Combine Interpack™ machinery and IPG long roll pressure-sensitive tape for greater value. Contact your authorized IPG distributor for details.



Scan for more info or visit itape.com/machines

