

DCP800A2PW

SPECIALTY POLYESTER DOUBLE-COATED TAPE

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

DESCRIPTION

Polyester (PET) film coated both sides with a pressure sensitive acrylic adhesive. Features a release treated Polyester (PET) film release liner (white).

PRODUCT APPLICATIONS

For permanent bonding of similar and dissimilar surfaces, including metal, wood, plastics and others. General mounting / splicing applications. Can resist short-term environmental temperature conditions up to +180°C (+356°F).

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	0.5 mil (25μ) PET
Adhesive	Solvent Acrylic
Adhesion to Steel (oz/in of width) PSTC-101	125 (35 N/25mm)
Adhesion to PE (oz/in of width)	61 (16.7 N/25mm)
Temperature Resistance - Localized	+356°F (180°C)
Temperature Resistance - Long Term	+175°F (80°C)
Total Thickness w/o liner (mils) PSTC-133	7.9 (0.2mm)
Liner Type / Thickness (mils) PSTC-133	PET- White 2.0 (0.05mm)
Color	Clear



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 06/13

