

H248B

DOUBLE-COATED TISSUE TAPE

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

DESCRIPTION

Tissue paper coated on both sides with pressure-sensitive acrylic adhesive. Provides good shear strength and adhesion and high initial tack allowing immediate/permanent bond to a variety of surfaces. Resists solvents and chemicals. Features an easy release 6 mil 80# PCK liner (white).

Product is not repulpable.

PRODUCT APPLICATION

Splicing of plastic film, paper and foil especially for applications that require adhesion to LSE surfaces such as PU, rubber, Neoprene, EPDM, etc. For application of heat breaking, gasketing and sealing; affixing plastic tiles, nameplates, trophy, emblems, labels and any application that requires the joining of two surfaces.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Tissue
Adhesive	Solvent Acrylic
Adhesion to Steel (oz/in of width) PSTC-101	77.6 (2.2 kg/25mm)
Total Thickness w/o Liner (mils) PSTC-133	5.1 (0.13mm)
Shear Adhesion to Steel (hours) 1" x 1" x 1 kg @ 77°F (25°C) PSTC-107	>24
Service Temperature	-22°F to +212°F (-30°C to +100°C)
Color	White



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com



While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 09/15

