

N2208

DOUBLE-COATED FOAM TAPE

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

DESCRIPTION

Cross-linked high density polyethylene, closed cell foam coated on both sides (double-coated) with a permanent bonding acrylic pressure-sensitive adhesive protected by an easy release treated 60# glassine paper liner (white). Adhesion allows permanent bond to a variety of irregular surfaces.

PRODUCT APPLICATION

Mounting and joining nameplates, signs, plaques, point-of-purchase, plastic hooks, etc. Long term mounting of mirror trims. General-purpose indoor/outdoor mounting and joining. For bonding and repair of metal or plastic articles (e.g. houseware, bathroom accessories, etc.).

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Closed cell / Cross-linked PE foam
Color	White
Adhesive	Solvent Acrylic
Adhesion to Steel (oz/in of width) PSTC-101	63.5 (1.8 kg/25mm)
Density (PCF)	6
Total Thickness w/o Liner (inch) PSTC-133	1/32" (0.8mm)
Shear Adhesion (hours) (1" x 1" x 1 kg @ 77°F (25°C)) PSTC-107	>24
Service Temperature (Long term)	-22°F to +194°F (-30°C to +90°C)



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 09/15

