

AC74 Carpet Tape

DOUBLE-COATED CLOTH TAPE

DESCRIPTION

Woven cloth coated on both sides with pressure-sensitive rubber adhesive that provides moderate adhesion and good initial tack to a variety of surfaces (including irregular and porous surfaces). The adhesive is formulated for clean, low residue removal from most surfaces. Features an easy release PE film liner (blue). **Product is not repulpable.**

PRODUCT APPLICATION

Temporary mounting, splicing, carpet tape (hold-down and position), manufacturing and engravers (temporary holding) and any application that requires the joining of two surfaces.

STORAGE RECOMMENDATION

Store new stock behind current stock. Store in a clean, dry place. Temperature of 70°F (21°C) +/- 6°F, and 40% to 50% relative humidity are recommended.

SHELF LIFE

When stored under recommended conditions, converted rolls have an expected shelf life of up to one year from date of shipment. Jumbo rolls have the same expected shelf life but it is recommended that they are converted within 6 months of date of shipment.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 06/20

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Woven Cloth
Adhesive	Natural Rubber
Adhesion to Steel (oz/in of width) PSTC-101 Exposed Side Lined Side	50 (13.7 N/25mm) 50 (13.7 N/25mm)
Tensile Strength (lbs/in of width) PSTC-131	42 (184 N/25mm)
Total Thickness w/o Liner (mils) PSTC-133	12.0 (0.30mm)
Liner Type and Color	PE film – Blue
Tape Color	Natural

