

ALF300L

3.0 MIL PREMIUM ALUMINUM FOIL TAPE WITH LINER

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

DESCRIPTION

3.0 mil dead soft aluminum foil with aggressive pressure-sensitive acrylic adhesive. Provides instant, water-resistant adhesion to clean, dry surfaces. Adheres well to itself (where overlapped) yet dispenses from the roll for easy application. Conforms to irregular/curved surfaces as it remains flexible and resists cracking and lifting. Also UV resistant. Recommended minimum application temperature: 35°F. Release coated kraft liner.

PRODUCT APPLICATION

Masking for chemical paint stripping of aircraft and use as underlay for PMB Blast Tape (drystripping process). Also can be used for electroplating (of aluminum), heat reflection/dissipation and to seam and seal fiberglass duct board, sheet metal ductwork, and flexible duct wrap to enhance appearance and maintain vapor barrier integrity. Other functions include HVAC (Heating, Ventilation, and Air Conditioning) and other Aerospace, Industrial, Marine and Appliance industry applications.

GOVERNMENT COMPLIANCE

BAC D6-34501, Rev. H
SAE-AMS-T-23397B. UL-723.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	3.0 mil Dead Soft Aluminum Foil
Adhesive	Acrylic
Tensile Strength (lbs/in width) PSTC-131	29 (127 N/25mm)
Elongation (% at break) PSTC-131	7.5
Adhesion to Steel (oz/in width) PSTC-101	55 (15 N/25mm)
Total Thickness w/o Liner (mil) PSTC-133	4.7 (0.12mm)
Operating Temperature Range	-30°F ~ +325°F (-34°C ~ +163°C)



While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 8/14