41392

SCRIM REINFORCED ADHESIVE TRANSFER TAPE

DESCRIPTION

A scrim reinforced water based acrylic adhesive system applied to a siliconized paper release liner. #41392 offers long term performance with very high adhesion to most surfaces. Hand tearable, thick adhesive transfer with scrim reinforcement. High adhesive strength to foams, PE & PP Films. Long term performance.

PRODUCT APPLICATION

Ideal for permanent bonding, splicing, laminating; adheres to fabric, wallboard, plastic, metal & wood. Used in carpet cove base installation.

This tape is not recommended to stick baseboards made of vinyl or rubber. Plasticizers in these substrates will cause the baseboards to fall off.

Product Sizes

150mm x 50m 25mm x 50m 38mm x 50m 90mm x 50m

intertape polymer group®

100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832 www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 03/24

INTERTAPE POLYMER GROUP®

TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing Polymer Fiber Scrim

Adhesive Water-based Acrylic

Total Thickness (mil) 9.2 (0.23 mm)

Adhesion (oz/in of width) 120 (2.899 kg/25mm)

Operating Temperature -40°F to +203°F (Continuous) -40°C to +95°C)

Short Term Temperature 248°F 120°C

Tape Color Translucent

Liner Siliconized Paper

