

# W208F

## FLAME RETARDANT ACRYLIC TRANSFER TAPE

### DESCRIPTION

Cactus® unsupported transfer tape W208F is an acrylic solvent based adhesive tape that is flame retardant, halogen free and offers exceptional resistance to high temperatures, chemicals and water permeation. An adhesive layer is directly coated onto the release liner providing excellent laminating results. This product is a UL94-V0 approved item (File NO. E250054)

### PRODUCT APPLICATION

Long term bonding for flame retardant applications on relatively smooth surfaces. Lamination to back of overlay materials in the automotive, electronics, foam and membrane switch markets



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 08/14

IPG®

# TECHNICAL DATA SHEET

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

<b>Backing</b>	No backing
<b>Adhesive</b>	Solvent Acrylic
<b>Total Thickness</b> w/o Liner	2.4 mil (0.06mm)
<b>Peel adhesion</b> (oz/in of width) PSTC-3	52.9 (1.5 kg/25mm <sup>2</sup> )
<b>Shear Strength</b> (hours) 1" x 1" x 2 kg 4.4 lbs PSTC-7	>72
<b>Service Temperature</b>	-40F to 248f (-40C to 120C)
<b>Tape Color</b>	White
<b>Liner</b>	White PCK

