



**MM**

### INDUSTRIAL GRADE TAPE

MM is the most versatile of the American® brand portfolio of masking tape for use within the automotive refinishing market. MM was specifically formulated to provide a secure bond to a multitude of surfaces while preventing lift or overspray while painting. The flexible green backing ensures conformable performance around any surface with ease. MM is capable of withstanding temperatures up to 300° F (149° C) for 30 minutes with clean removal. For the best finish, get the best start with American Brand MM!



### FEATURES & BENEFITS


- Smooth, consistent unwind
- Flexible backing for excellent conformability and ease of application
- Specialized adhesive platform that ensures clean, one-piece, removal
- Excellent wet sanding properties
- Low profile light green backing for superior visibility of masked areas
- Heightened bonding to backing for increased shingling performance



CONFORMABLE



HAND TEARABLE



STRONG HOLD



REMOVES CLEANLY



SMOOTH UNWIND



888-898-7834 | itape.com



©2025 IPG® • MM • 021725

## PRODUCT ATTRIBUTES

PRODUCT STYLE	BACKING	ADHESIVE	TOTAL THICKNESS	TENSILE STRENGTH	ADHESION TO STEEL	ELONGATION	TEMPERATURE RESISTANCE
			mils	lb/in of width	oz/in of width	% at break	
MM	Crepe Paper	Natural rubber/Resin	6.0	22	35	10	300°F (149°C)

RESOURCE NUMBER	SIZE	ROLLS PER CASE
MM1855	18mm x 54.8m	48 rolls
MM2455	24mm x 54.8m	36 rolls
MM3655	36mm x 54.8m	24 rolls
MM4855	48mm x 54.8m	24 rolls



## PRODUCT APPLICATIONS

- Paint masking requiring adhesion to and removal from a variety of surfaces
- Wet sanding

## MARKETS

- Automotive
- Truck
- Bus
- RV
- Marine
- General Manufacturing
- Industrial



Scan for more info or visit [itape.com/american](http://itape.com/american)

